

Agricultural Tire

InfinityTM

powered
by **AL DOBOWI**





Infinity[™]
powered by **AL DOBOWI**

Radial Agricultural Tire



LR861

Radial Agricultural Tire

1. Better traction and braking performance.
2. Save work time and fuel.
3. Better running stability.
4. Suitable for modern mechanical equipment.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
420/80R46	145/142	A8/B	W13	2900	160	1840	418	47.0
420/80R46	151/148	A8/B	W13	3450	240	1840	418	47.0
480/80R42	151/151	A8/B	DW16L	3450	160	1835	479	49.0
480/80R42	156/156	A8/B	DW16L	4000	240	1835	479	49.0
480/80R46	156/158	A8/B	DW16L	4250	240	1936	479	49.0
280/85R24	115/112	A8/B	W10	1215	160	1086	282	39.0
320/85R24	122/119	A8/B	W11	1500	160	1154	319	41.0
320/85R28	124/121	A8/B	W11	1600	160	1255	319	41.0
320/85R32	126/123	A8/B	W11	1700	160	1357	319	41.0
320/85R32	142/139	A8/B	W11	2650	400	1357	319	41.0
320/85R36	128/125	A8/B	W11	1800	160	1458	319	41.0
340/85R24	125/122	A8/B	W12	1650	160	1186	343	42.0
340/85R28	127/124	A8/B	W12	1750	160	1289	343	42.0
340/85R32	142/139	A8/B	W12	2650	360	1391	343	42.0
340/85R36	132/129	A8/B	W12	2000	160	1492	343	42.0
340/85R38	133/130	A8/B	W12	2060	160	1543	343	42.0
380/85R24	131/128	A8/B	W12	1950	160	1256	380	45.0
380/85R28	133/130	A8/B	W12	2060	160	1357	380	45.0
380/85R30	135/132	A8/B	W12	2180	160	1408	380	45.0
380/85R34	137/137	A8/B	W12	2300	160	1510	380	45.0
380/85R34	147/147	A8/B	W12	3075	240	1510	380	45.0
420/85R24	137/134	A8/B	W15L	2300	160	1324	418	48.0
420/85R28	139/136	A8/B	W15L	2430	160	1425	418	48.0
420/85R30	140/137	A8/B	W15L	2500	160	1476	418	48.0
420/85R34	142/139	A8/B	W15L	2650	160	1578	418	48.0
420/85R36	144/141	A8/B	W15L	2800	160	1679	418	48.0
460/85R30	145/142	A8/B	W16L	2900	160	1544	455	51.0
460/85R34	147/144	A8/B	W16L	3075	160	1646	455	51.0
460/85R36	149/146	A8/B	W16L	3250	160	1747	455	51.0
460/85R42	150/147	A8/B	W16L	3350	160	1849	455	51.0
460/85R46	152/149	A8/B	W14L	3550	160	1943	464	51.0
460/85R46	158/155	A8/B	W14L	4250	240	1943	464	51.0
520/85R38	155/152	A8/B	DW16L	3875	160	1849	516	54.0
520/85R42	157/154	A8/B	DW16L	4125	160	1951	516	54.0
520/85R42	167/164	A8/B	DW16L	5450	240	1951	516	54.0
320/90R46(R-1)	146/143	A8/B	W10	3000	320	1744	319	37.0
320/90R46(R-1)	148/148	A8/B	W10	3150	360	1744	319	37.0
380/90R46	149/149	A8/B	W12	3250	240	1852	380	45.0
380/90R46	157/157	A8/B	W12	4125	360	1852	380	45.0
420/90R30	142/139	A8/B	DW13	2650	160	1518	418	48.0
420/90R30	147/144	A8/B	DW13	3075	240	1518	418	48.0
320/90R46(R-1)	146/143	A8/B	W10	3000	320	1744	319	37.0
320/90R46(R-1)	148/148	A8/B	W10	3150	360	1744	319	37.0
340/85R38	133/130	A8/B	W11	2060	160	1543	343	42.0
380/90R46	149/149	A8/B	W12	3250	240	1852	380	45.0
380/90R46	157/157	A8/B	W12	4125	360	1852	380	45.0

* Not all sizes / index are available for EU, Check with your Sales Manager.



Infinity™
powered by **AL DOBOWI**



LR650

Radial Agricultural Tire

1. Longer service life.
2. Excellent stability and comfort.
3. More efficient traction.
4. Outstanding floating behavior reduces pressure to land.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
440/65R24	128/131	D/A8	W14L	1800	160	1182	441	45.0
440/65R28	131/134	D/A8	W14L	1950	160	1283	441	45.0
480/65R24	133/136	D/A8	W15L	2060	160	1234	479	46.0
480/65R28	136/139	D/A8	W15L	2240	160	1335	479	46.0
540/65R24	140/143	D/A8	W16L	2500	160	1312	550	48.0
540/65R28	142/145	D/A8	W16L	2650	160	1413	550	48.0
540/65R30	150/153	D/A8	W16L	3350	240	1464	550	48.0
540/65R34	145/148	D/A8	W16L	2900	160	1566	550	48.0
600/65R28	147/150	D/A8	DW20B	3075	160	1491	591	52.0
600/65R38	153/156	D/A8	DW20B	3650	160	1745	591	52.0
650/65R38	157/160	D/A8	DW20B	4125	160	1811	645	56.0
650/65R42	165/168	D/A8	DW20B	5150	240	1913	645	56.0
710/70R38	166/169	D/A8	DW23B	5300	160	1959	716	57.0
710/70R42	168/171	D/A8	DW23B	5600	160	2061	716	57.0
710/70R42	173/176	D/A8	DW23B	6500	240	2061	716	57.0



LR700

Radial Agricultural Tire

1. Saving time and fuel.
2. Better self-cleaning capability.
3. Comfort on the road and in the field.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
360/70R24	122/119	A8/B	W11	1500	160	1152	357	42.0
360/70R24	127/124	A8/B	W11	1750	240	1152	357	42.0
380/70R24	125/125	A8/B	W12	1650	160	1190	380	43.0
420/70R24	130/127	A8/B	W13	1900	160	1248	418	44.0
420/70R24	136/133	A8/B	W13	2240	240	1248	418	44.0
420/70R28	133/130	A8/B	W13	2060	160	1349	418	44.0
420/70R28	139/136	A8/B	W13	2430	240	1349	418	44.0
480/70R24	138/135	A8/B	W15L	2360	160	1316	479	47.0
480/70R28	140/137	A8/B	W15L	2500	160	1421	479	47.0
480/70R28	145/142	A8/B	W15L	2900	240	1421	479	47.0
480/70R28	151/148	A8/B	W15L	3450	320	1421	479	47.0
480/70R34	143/143	A8/B	W15L	2725	160	1580	479	47.0
480/70R38	145/142	A8/B	W15L	2900	160	1681	479	47.0
520/70R38	150/150	A8/B	W16L	3350	160	1749	516	48.0
580/70R38	155/155	A8/B	W18L	3875	160	1827	577	50.0
580/70R38	170/167	A8/B	W18L	6000	280	1827	577	50.0



LR451

Radial Agricultural Tire

1. Increase traction performance.
2. Enhance shoulder wear and cut resistance performance.
3. Enhance tread wear resistance performance.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
460/70R24 IND	152/152	A8/B	DW14L	3550	320	1254	455	32.0
460/70R24 IND	159/159	A8/B	DW14L	4375	400	1254	455	32.0

* Not all sizes / index are available for EU, Check with your Sales Manager.



LR8000

Radial Agricultural Tire

1. Longer service life.
2. Excellent stability and comfort.
3. More efficient traction.
4. Outstanding floating behavior reduces pressure to land.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
800/65R32	167	D	DW27B	5450	160	1853	798	58.0



FL300

New

Radial Agricultural Tire

1. STEEL BELTED
2. Wear and puncture resistance.
3. Good grip and self-cleaning performance.

Size	Load Index	Speed Symbols	Rim	Max.Load (kg)	Inflated Pressure (kPa)	Overall Diameter (mm)	Section Width (mm)	Tread Depth (mm)
560/60R22.5 IMP	165	D	AG16.00	5150	500	1244	543	18.0
560/45R22.5 IMP	152	D	AG16.00	3550	400	1076	543	18.0
500/60R22.5 IMP	155	D	AG16.00	3875	400	1172	503	18.0

* Not all sizes / index are available for EU, Check with your Sales Manager.

Infinity[™]
powered
by **AL DOBOWI**



InfinityTM
powered
by **AL DOBOWI**[®]

Al Dobowi Group
P.O. Box 61348
Dubai / United Arab Emirates

Avoca Motor Products
Parkway 4 Longbridge Road, Trafford Park
Manchester, M17 1SN / United Kingdom

Eskay Spain S.L.U
Paseo de la Castellana 79, Planta 7ª
PC 28.046 Madrid / Spain

infoeurope@infinitytyres.com
www.aldobowi.eu

